

Mechanical Data

Item	Dimension	Unit
Module dimension	80.0 x 36.0 x 10.0(MAX)	mm
View area	66.0 x 16.0	mm
Active area	56.95 x 6.35	mm
Mounting hole	75.0 x 31.0	mm
Dot size	0.55 x 0.75	mm
Dot pitch	0.60 x 0.80	mm
Character size	2.95 x 6.35	mm
Character pitch	3.6 x 6.35	mm

Absolute Maximum Rating

Item	Symbol	Min	Max	Unit	Notes
Input Voltage	V_i	-0.3	VDD	V	
Supply Voltage For Logic	VDD-Vss	-0.3	5.3	V	

Electronical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For Logic	VDD-VSS	-	3.0	5.0	5.3	V
Input High Volt.	V_{IH}	-	0.9 VDD	-	VDD	V
Input Low Volt.	V_{IL}	-	GND	-	0.1VDD	V
Output High Volt.	V_{OH}	$I_{OH}=-0.5mA$	0.8 VDD	-	VDD	V
Output Low Volt.	V_{OL}	$I_{OL}=0.5mA$	GND	-	0.2 VDD	V
Supply Current	I_{DD}	VDD=5V	-	15	-	mA

Feature

- 5x8 dots includes cursor
- Built-in Controller RS0010
- +5V power supply
- 1/8 duty cycle
- Interface: 6800, option 8080 & SPI
- Sunlight readable & polarizer optional

Pin No.	Symbol	Description
1	VSS	Ground
2	VDD	Supply Voltage for logic
3	NC	
4	RS	H: DATA, L: Instruction code
5	$\overline{R/W}$	H: Read(MPU←Module) L: Write(MPU→Module)
6	E	H→L Enable signal
7	DB0	Data bit 0
8	DB1	Data bit 1
9	DB2	Data bit 2
10	DB3	Data bit 3
11	DB4	Data bit 4
12	DB5	Data bit 5
13	DB6	Data bit 6
14	DB7	Data bit 7
15	NC	
16	NC	

OLED Character type

REC001601A OLED Character 16x1 dots

Dimension drawing

